



ACCENT FLOOR HEATING CABLE 150

Part Code: ATC-150
Accent Cable
150 Watts

OVERVIEW

The Accent Cable is designed for awkward or small areas where a mat cannot be used.

Manufactured in a wide range of ready-made sizes and with the supply lead wire at one end only. It is supplied in a roll for quick and easy installation.

This design offers maximum flexibility to the installer; is easy to plan and lay; and is suitable for large or small areas.

Note: This heater cannot be cut or shortened.

KEY FEATURES

- Designed for areas too small for matting.
- Ideal as an economical single heat source
- One simple connection cable
- Supplied with fixing tape
- One of the thinnest on the market at just 3.8mm
- Twin conductor
- 3m Cold tail
- FEP (Fluoropolymer) cable jacket
- Available from 12.5m to 150m
- 25 Year cable warranty



ACCENT FLOOR HEATING CABLE 150

SPECIFICATIONS

Output	12W/m ²
Thickness	3.8mm Wire
Voltage	230V
Max. Temperature Output	+80°C
Warranty	25 Year cable warranty
Protection Class	1 RCD
Connection	One side connection
Colour	Blue
Last Insulation	PVC

CABLE LOADINGS

PART NO:	CABLE LENGTH (M)	Floor Area (M ²)				TOTAL WATTS	TOTAL AMPS	TOTAL CABLE RESISTANCE (OHMS)
		100w/m ² (120mm spacings)	120w/m ² (100mm spacings)	150w/m ² (80mm spacings)	200w/m ² (60mm spacings)			
ATC-150-1	12.5	1	1.25	1	0.75	100	0.65A	352.67Ω
ATC-150-1.5	18.8	2	1.88	1.5	1.13	200	0.97A	235.11Ω
ATC-150-2	25	3	2.5	2	1.25	300	1.30A	176.33Ω
ATC-150-2.5	31.3	3.75	3.10	2.5	1.88	400	1.60A	141.07Ω
ATC-150-3	37.5	4.5	3.75	3	2.25	600	1.90A	117.56Ω
ATC-150-3.5	43.8	5.1	4.38	3.5	2.63	800	2.28A	100.76Ω
ATC-150-4	50	6	5	4	3	1000	2.60A	88.17Ω
ATC-150-5	62.5	7.5	6.25	5	3.75	1200	3.26A	70.53Ω
ATC-150-6	75	9	7.5	6	7.5	1500	3.91A	58.78Ω

